



Den Braven



Better results through Knowledge

Technical Data Sheet

Zwaluw Plasterboard Filler

Lightweight Filler



Product Description

Zwaluw Plasterboard Filler is a virtually non shrinking , ready to use ultra light, ready mixed filler and spackling compound for filling and repairing cracks and holes in walls and ceilings.

Benefits

- ▶ Non-Shrinking
- ▶ Lightweight
- ▶ Sandable
- ▶ Excellent paintability

Applications

Zwaluw Plasterboard Filler can be used for filling in one time of joints and screw holes in plasterboard walls and ceilings. For filling, repairing and smoothening holes and static joints in one application in concrete, brickwork and stucco layers.

Technical specifications

Application Temperature		+5°C till +30°C
Base		Acrylic dispersion
Density		0,57 g/ml
Flow	ISO 7390	< 2 mm
Skin Formation		5 minutes @ 23°C/ 55% RH
Temperature Resistance		-20°C till +75°C

Limitations

- ▶ Painting over with highly filled emulsion paints can cause cracks in the paint film.
- ▶ Not recommended for application on PE, PP, PC, PMMA, PTFE and bituminous surfaces, underwater applications and for expansion joints.

Joint Designs

Surface Preparations and Finishing

Before using the Zwaluw Plasterboard Filler refer to the Health & Safety Sheet. All surfaces must be clean, dry and free from dust, grease and other loose material. Adhesion tests prior to the application are recommended.

Clean the surfaces thoroughly by using Zwaluw Cleaner (PDS 7.82). Stir Zwaluw Plasterboard Filler in pots and buckets before application and add some drops of water if necessary. Apply Zwaluw Plasterboard Filler with a putty knife. Finish with a wet taping knife or a wet trowel. Apply with a professional Zwaluw Caulking Gun (PDS 7.01). Smoothen the fresh applied sealant within the skin forming time to ensure a firm and full contact with the joint faces. For some applications an extra finish after drying can be necessary.

Cleaning

Uncured material and tools can be cleaned by using a damp cloth. Cured material can be cleaned with Zwaluw Cleaner (PDS 7.82).

Colour(s)

- ▶ White

Den Braven Sealants B.V.

Denariusstraat 11| 4900 AD Oosterhout | The Netherlands

T +31 (0) 162 - 491 000 | E info@denbraven.com



Den Braven



Better
results
through
Knowledge

Technical Data Sheet

Zwaluw Plasterboard Filler

Lightweight Filler

Colour(s)

White

Packaging

Cartridge 310 ml

Shelf Life

Storage between +5°C and +25°C and in shaded conditions. Shelf life of the Zwaluw Plasterboard Filler is 12 months when stored as recommended in original unopened packaging.

Health & Safety

Product Health and Safety Data Sheet must be read and understood before use. These are available on request and via the Den Braven websites.

Warranty & Guarantee

Den Braven warrants that its product complies, within its shelf life, to its specification.

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Den Braven Sealants B.V. ("Den Braven"). No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Den Braven's written consent. The technical information in this document serves as an indication and is non-exhaustive. Den Braven is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Den Braven reserves the right to amend the wording of this document. Den Braven cannot be held liable for any damage, either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

Den Braven Sealants B.V.

Denariusstraat 11 | 4900 AD Oosterhout | The Netherlands

T +31 (0) 162 - 491 000 | E info@denbraven.com