



## Technical Data Sheet

### Zwaluw Aluband

Self adhesive modified bituminous flashing



#### Product Description

Zwaluw Aluband is a strong self adhesive flashing of a modified bituminous layer with a top cover of strong weather resistant, aluminium or lead coloured polyester foil, and an easily removable siliconised high density polyethylene release foil underneath.

#### Benefits

- Adheres well to almost all substrates
- Paintable
- Available in multiple sizes
- UV-resistant

#### Applications

Zwaluw Aluband can be used for flashing gutters, bay windows, between walls and extensions. Zwaluw Aluband instantly bonds to many surfaces. It is easily applied in the desired shape. The foil is weather resistant and has a high tear resistance.

#### Directions Of Use

General rule is to add 100 mm to the joint width, 50 mm for both sides. Minimum overlap between Zwaluw Aluband strips is at least 25mm. For a complete overview see our website or contact Den Braven.

#### Additional information

Application temperature	0 °C to +35 °C
Density	1,40 g/m2
Frost resistance during transportation	Up to -15 °C
Temperature resistance	-40 °C to +80 °C

*These are typical values*

#### Limitations

- Not suitable for PE, PP, PC, PMMA and PTFE

#### Surface Preparations and Finishing

Before using the Zwaluw Aluband refer to the Health & Safety Sheet. All surfaces must be clean, dry and free of dust, grease and other loose material. Adhesion tests prior to application are recommended. Thoroughly clean by using Zwaluw Cleaner and two cloths. Porous surfaces should be primed with Zwaluw B&B Primer Universal or Zwaluw B&B Spray Primer Universal. Contact Den Braven for a full recommendation. Clean the surfaces thoroughly by using Zwaluw Cleaner. If necessary use a primer.

#### Cleaning

Surfaces, material and tools can be cleaned by using Zwaluw Cleaner.

#### Colour(s)

- Aluminium

#### Packaging

- Roll

*For product specifications, please refer to the Product Detail Page*

#### Shelf Life

Storage between +5 °C and +25 °C and in shaded conditions. Shelf life is 36 months when stored as recommended in original unopened packaging.

#### Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

#### Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

#### Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.