

**Introduction**

SealXpert® SP70 Varnishcote is formulated to protect printed circuit boards against creepage and short circuits. The acrylic insulating film is resistant to diluted acids, alkalies, alcohol and humidity.

**Features**

- Excellent corrosion protection
- Lengthen useful life of equipment
- High temperature resistant
- Drip proof
- Can be soldered through

**Typical Applications**

- Protect printed circuit board against creepage and short circuits
- Protect components and equipment from condensation and moisture
- Insulates cables and wires
- Protect marine radio and other components against salt water corrosion

**Typical Properties**

Colour:	Clear / Red
Odour:	Solvent odour
Flash point:	10°C
Boiling point:	80°C
Vapour density:	> 1 (Air = 1)
Specific gravity:	0.90
Solubility:	Slightly Soluble

**Direction for Use**

1. Shake well before and during use.
2. De-energise; DO NOT use on energised equipment
3. Mask area not to be sprayed.
4. Spray from a distance of 30 to 45cm in light, even coats.
5. Additional coats for additional protection may be applied after each coat dries.
6. Allow 30 minutes drying between coats to facilitate build up.
7. When finished spraying, clean valve by turning can upside down and pressing actuator until only propellant escapes.

**Safety and Handling Consideration**

Do not puncture, incinerate or store above 50°C (120°F). Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Flammable aerosol. Keep away from heat, sparks, open flames, hot surfaces. Do not spray on open flame or other ignition source. Use only in well ventilated area. Avoid continuous breathing of vapour and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn.

In case of contact with eyes or skin, rinse with clean water immediately; if symptom goes on, call a physical attention.

Keep away from children.

More details, please refer to MSDS of this product

**Recommended Storage:**

Stored in a cool and dry location in unopened containers at 8~28°C. Keep away from flame or heat sources. Shelf life is 36 months

Disclaimer: The information contained herein is considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data, the results to be obtained by the use thereof, or that any such use will not infringe any patent. Before using, user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith.