

Introduction

Wrap Seal® ULTRA Quick Repair Kit for Active Pipe Leaks is a leak repair system that no shutdown required. It applicable on any metal or non-metal pipes and used in many industries such as oil and gas, petrochemical, offshore, marine, etc.

Features

- Repairs under active leak up to 150 psi (11 kg/cm²) pressure
- Applicable to pipes up to 18" (457 mm) diameter
- Withstand pressure up to 500 psi (35 kg/cm²)
- Withstand temperature up to 200 °C (392 °F)
- Safe for drinking water and resistant to most chemicals
- Ideal for pipeline reinforcement

Typical Properties

Operating temperature	-50 °C to 200 °C (-58 °F to 392 °F)
Tensile strength	3,920 psi (276 kg/cm ²)
Bond strength	230 psi (16 kg/cm ²)
Compression strength	13,750 ± 530 psi (967 ± 37 kg/cm ²)
Yield strength	2,260 psi (159 kg/cm ²)
Cured hardness	82 Shore D
Dielectric strength	400 Volts/mil

Application

- Pipe repairs:
 - active pipe leaks
 - sealing joints
 - hazardous material spill control
 - reinforce thinning walls
- Repairs in hard to reach areas
- Underwater repairs

Directions for Use

- Minimize the flow rate and reduce system pressure
- Roughen the area to be repaired
- Knead the Seal Stic®
- Place the Seal Stic® away from the leak location
- Start wrapping the SealXpert® Ultra Sealing Tape a few distances away from the leak location
- Continue to wrap SealXpert® Ultra Sealing Tape onto pipe while pushing the Seal Stic® onto leak location
- Immerse Wrap Seal® Fiberglass Tape into water
- Wrap the Wrap Seal® Fiberglass Tape above the repair tape as tightly and evenly as possible, using the entire roll

- Discard the plastic tube at the end of the roll
- Wet gloves in water and quickly compress the bubbling resins back into the fiberglass wrap until all bubbling has stopped.
- Repair completed with smooth and hard ivory appearance

Safety and Handling Consideration

This resin contains ingredients which could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn. SealXpert® maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers.

Our Material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using SealXpert® products in your facilities.

Recommended Storage

Store at temperatures below 35°C/ 95°F. Storage life decreases with increasing storage temperature. Avoid exposure to heat sources such as direct sunlight or steam pipes. To avoid contamination of product with water, do not store outdoors. Keep sealed to prevent moisture pick-up and monomer loss.

Package

- 1 roll of Wrap Seal® Fiberglass Tape
 - 2" x 6' (50 mm x 1.8 m)
 - 2" x 12' (50 mm x 3.6 m)
 - 3" x 9' (75 mm x 2.7 m)
 - 4" x 12' (100 mm x 3.6 m)
- 1 roll of SealXpert® Ultra Sealing Tape
 - 1" x 16' (25 mm x 5 m)
 - 1" x 16' (25 mm x 5 m)
 - 1¼" x 16' (32 mm x 5 m)
 - 2" x 16' (50 mm x 5 m)
- 1 unit of Seal Stic® Quick Cure Epoxy
- 1 pair of latex gloves
- Operating instruction

Disclaimer: The information contained herein is considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data, the results to be obtained by the use thereof, or that any such use will not infringe any patent. Before using, user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith.